

# Standard **KEGS LLC**

No.	Specification	Details	Note
<b>4 Matic</b>			
1	Demension	217 x 140 x 237cm Height	
2	Weight	500KGS	
3	Power Input	3 phase 208v 60HZ	
4	Power Consumption	15.5KW	
5	Power Port	3P+N+G	
6	Material	SUS304	
7	Coupler	--	
8	Hose Material	--	
9	Low-voltage apparatus	Omron	
10	Heating Method and Consumption	Electrical heating / 6KW/pc (in Caustic tank and hot	
11	Liquid Tank Volume	2 x 135L	
12	Motor + Pump	SUS304 high temp pump head	
13	Temperature sensor	PT100	
14	Thermo Control	EVCO Italy EVK401V7	
15	Control	Siemens PLC200 Smart +Smart IEV7	
16	Connection types	1.5" Tri-clamp	
17	Spear Type	D Type	
18	Keg Sizes	AMERICAN 20L-60Lkeg	
21	Freight Packaging	Wooden composite crate	



	Basic Hardware	Two pumps, two tanks w/o insulation, hot water/cold water connect from external source	
	Working Procedure	<b>CLEANING PROCEDURE:</b> CONTACT → DE-ULLAGE → RINSE/DRAIN → DE-ULLAGE → CAUSTIC → DE-ULLAGE → HOT WATER RINSE 1 → DE-ULLAGE → HOT WATER RINSE 2 → DE-ULLAGE → SANITIZER RINSE/DRAIN OFF → CO2 DE-ULLAGE → CO2 BACK PRESSURE → CYLINDER RETURN	
	Ex Work	\$	22,800.00